



## Quartzell™ BenchBases

The high resolution Quartzell<sup>™</sup> transducers employed by the 3600 Series Bench Bases are what allow them to be type approved at 10,000 divisions.



# 3600 Series Quartzell<sup>™</sup> Bench Bases

# 3600 Series QDT Bench Bases

#### Feature and benefits

**Quartzell transducers**—High resolution, digital output from a rugged load cell structure.

*Ouartzell* ™

**Type approved "T" models to 10,000 d**—Ideal for any certified weighing transaction such as shipping or mailing operations.

**New tasks for a standard bench base**—Use the Quartzell base as a high resolution remote base for your PC-810 Counting Scale. Or link it to a WI-130 Indicator or any Quartzell compatible instrument for new levels of weighing sensitivity.

**Stainless steel shroud**—Resists damage; maintains its good looks for years.

**DuraBridge construction**—On heavy capacity 18 x 18-inch decks. Deck deflection is less than <sup>1</sup>/<sub>2</sub>-inch. Minimizes off-center loading error.

#### Options

**Ball-top shroud**—For conveyor systems, speed processing. Reduce lifting to a minimum.

### Specifications

Model	Capacity		Dimensions
3633T*	10lb	(5 kg)	12" x 14"
	50 lb	(25 kg)	
	100 lb	(50 kg)	
3633	150 lb	(80 kg)	12" x 14"
3635	200 lb	(110 kg)	18" x 18"
	300 lb	(165 kg)	

\* The 3633T-10 lb version has an 8" dia. round stainless steel platter and comes standard with a distributor-installed draft shield.

Note: The "T" in the model number indicates type approval

#### **Construction:**

Models 3633T & 3633: Die cast aluminum with stainless steel shroud

Model 3635: Mild steel with stainless steel shroud

Environment: -10°C to 40°C (14°F to 104°F)

Agencies: NTEP Class III at 10,000 d and NTEP Class II at 11,000 d (Model 3633T) Certificate of Conformance #95-071A1



Fairmont, Minnesota U.S.A. USA Toll-Free: 800-368-2039 USA Phone: 507-238-4461 www.wtxweb.com

Pointe Claire, Quebec Canada CAN Toll-Free: 800-561-9461 CAN Phone: 514-695-0380 www.weigh-tronix.ca

