

6103 Perfect portions, more efficient operations

Small footprint is a great advantage where counter space is at a premium. Use the 6103 to build consistent products and control ingredient costs – enhance customer satisfaction and maximize profitability.

- Innovative "Touchless" Zero Mechanism Just wave or place your hand over the display to zero the scale.
- Easy to Clean Removable stainless steel platter, detachable display and bracket.
- Full Capacity Zero Weigh each ingredient as it is added.

The Model 6103 is perfect for use in pizza parlors, sandwich and salad shops, bakeries, convenience stores, delicatessens, restaurants, bars - anywhere portion control is required to maintain product quality and save on ingredient costs. Get accurate weight measurements every time, while the innovative "touchless" zero mechanism increases operator efficiency, greatly extends life of the scale, and enhances food handling safety.

Features & Benefits

- Innovative "Touchless" Zero Mechanism Just wave or place your hand over the display to zero the scale. This feature significantly improves hygiene, while eliminating the physical wear and tear on a normal button switch mechanism.
- **Easy to Read** Angled six digit LCD display with large 0.5" (12 mm) characters.
- Easy to Use User friendly interface keeps operation simple and reduces training time.
- Easy to Clean Removable stainless steel platter, detachable display and bracket.
- Accurate Weigh anywhere on the platter even in all four corners.
- Full Capacity Zero Weigh each ingredient as it is added.
- Superior Durability / Quality Construction Stainless steel weighing area with welded corners and full skirt around perimeter of the base. Heavy-duty load cell and load stop mechanism ensures long life.
- **Options** Several display location options (below), footswitch, standard zero button. See separate options sheet for details.



- Low Profile Only 2.5" (64 mm) tall. Perfect for use on top or recessed into prep table.
- Internally Configurable Units of Measure Decimal pounds, ounces, or grams.
- I/O Port RS-232 serial output for interface to software programs, enabling inventory control.

Specifications

- Capacity/Resolution Factory Set As: 240 oz x 0.1 oz
- Optional Capacities/Resolutions
 Pounds: 10 lb x 0.005 lb; 15 lb x 0.005 lb; 25 lb x 0.01 lb
 Ounces: 400 oz x 0.25 oz; 160 oz x 0.05 oz
 Grams: 3000 g x 1 g; 6000 g x 2 g; 10000 g x 5 g
- Dimensions

Weigh platter dimensions: 6" x 10" (152 mm x 254 mm) Base dimensions: 6.4" x 10.4" (163 mm x 264 mm) Adjustable height: 2.5" – 3" (64 mm – 76 mm) Remote display enclosure: 5.8" (W) x 3.0" (H) x 1.4" (D max) (147 mm x 75 mm x 36 mm)

Power

120 VAC (+10%, -15%) 60Hz (+/- 3Hz). Wall mount supply. Standard 3 wire with ground input.

Output

15 VDC @ 0.3 Amps minimum 10% – 90% RH, (non-condensing)

- Operating Environment
 41°F 104°F (5°C 40°C)
 10% 90% RH, (non-condensing)
- Agency Approvals
 UL Listed, CSA Certified Power Supply.
 NSF Approved.
 NOT Legal for Trade.
- See separate sheet for standard configurations.



Product complies

with F.C.C.

Avery Weigh-Tronix (Retail North America) 1000 Armstrong Drive Fairmont, MN 56031

PH Toll-Free: 800-237-1886 PH: 507-238-4461 FAX Toll-Free: 800-237-2063 FAX: 507-238-8756

E-mail: sales@AveryBerkelUSA.com Internet: www.AveryBerkelUSA.com

4/05 pos6103_l.indd PN 07015-0016A e1 Printed in USA

© Avery Weigh-Tronix 2004. All rights reserved. This publication is issued to provide outline information only which, unless agreed by Avery Weigh-Tronix in writing, may not be regarded as a representation relating to the products or services concerned. Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.