

## 6115

## Perfect pizzas and a healthier bottom line

Great for use in food service operations to build consistent products and help control costs, thereby maximizing customer satisfaction and profitability.



he Model 6115 is perfect for use in pizza parlors, sandwich and salad shops, bakeries, supermarkets - anywhere portion control is required to maintain product quality and save on ingredient costs. The innovative "touchless" zero mechanism increases throughput, greatly extends the life of the scale and significantly enhances food handling safety.

## Features & Benefits

- Innovative "Touchless" Zero Mechanism Just wave or place your hand over the display to zero the scale. This feature significantly improves hygiene, while eliminating the physical wear and tear on a normal button switch mechanism.
- Easy to Read Angled six digit LCD display with large 0.5" (12 mm) characters.
- Easy to Use User friendly interface keeps operation simple and reduces training time.
- Easy to Clean Removable stainless steel platter, detachable display and bracket.
- Accurate Weigh anywhere on the platter – even in all four corners.
- Full Capacity Zero Weigh each ingredient as it is added.
- Superior Durability / Quality Construction Stainless steel weighing area with welded corners and full skirt around perimeter of the base. Heavy-duty load cell and load stop mechanism ensures long life.
- Low Profile Only 2.5" (64 mm) tall. Perfect for use on top or recessed into prep table.
- **Pan / Tray Stops** Keeps product in center of scale.
- **Unique Design** Three legged stool design keeps scale stable on any surface.
- Power Supply Internally mounted with standard wall plug. No large wall adapter to plug in or take up two receptacle spaces.
- Internally Configurable Units of Measure Decimal pounds, ounces, or grams.
- I/O Port RS-232 serial output for interface to software programs, enabling inventory control.

**Options** Several display location options (below), footswitch, standard zero button. See separate options sheet for details.







## **Specifications**

Capacity/Resolution Factory Set As: 240 oz x 0.1 oz

 Optional Capacities/Resolutions Pounds: 15 lb x 0.005 lb; 25 lb x 0.01 lb Ounces: 400 oz x 0.25 oz;

Grams: 6000 g x 2 g; 10000 g x 5 g

**Dimensions** 

Weigh platter dimensions: 13" x 13" (330 mm x 330 mm) Base dimensions: 13.4" x 13.4" (340 mm x 340 mm) Adjustable height: 2.5" – 3" (64 mm – 76 mm) Remote display enclosure:

5.8" (W) x 3.0" (H) x 1.4" (D max) (147 mm x 75 mm x 36 mm)

Power

120 VAC (+10%, -15%) 60Hz (+/- 3Hz). Internally mounted adapter. Standard 3 wire with ground input.

15 VDC @ 0.3 Amps minimum 10% – 90% RH, (non-condensing)

Operating Environment

41°F - 104°F (5°C - 40°C) 10% – 90% RH, (non-condensing)

Agency Approvals

UL Listed, CSA Certified Power Supply. NSF Approved. NOT Legal for Trade.

See separate sheet for standard configurations.



**Avery Weigh-Tronix** (Retail North America) 1000 Armstrong Drive Fairmont, MN 56031

**PH Toll-Free:** 800-237-1886

PH: 507-238-4461

FAX Toll-Free: 800-237-2063 **FAX:** 507-238-8756

**E-mail:** sales@AveryBerkelUSA.com

