

WEIGH-TRONIX



Baggage Scale

Baggage Scale

Features and benefits

Three standard platform sizes — Fit most existing counters. Custom sizes are available to suit specialized applications.

Single load cell design — No moving parts for low maintenance.

Overload stops — Prevent scale damage from excessive loads or dropped objects.

Stainless steel shroud — It's tough, and easy to clean.

Options

Side rails — Four inches high. Added to the deck surface to prevent baggage from resting on counter sides resulting in incorrect weights.

RD-190 remote displays — Use up to three additional displays to provide added convenience for both customer and operator. Allows one scale to be easily used by two operators.

Specifications

Standard sizes:

22 x 27 x 5.4 in (55.8 x 68.6 x 13.7 cm)
22 x 29 x 5.4 in (55.8 x 73.6 x 13.7 cm)
27 x 30 x 5.4 in (68.6 x 76.2 x 13.7 cm)

Standard capacities:

300 x 0.1 lb (150 x 0.05 kg)
500 x 0.2 lb (250 x 0.01 kg)

Base construction:

Painted mild steel, stainless steel shroud

Indicator:

LCD, 0.5 inches high, 12 ft interface cable from base to display

Surface mount display dimensions:

4 x 7.6 inch with a cutout of 3.4 x 6.2 inches
(10.2 x 19.4 cm with cutout of 8.6 x 15.7 cm)

Controls:

Push-button zero with auto zero tracking
Push-button lb/kg selection, push-button on/off

Annunciators: Center zero, unit of measure

WI-190 weight display — Simple and fast. With 1/2 inch LCD characters and controls for push-button zero, lb/kg selection and display on/off.

Lb/kg operation — Single push-button assures easy selection for use on both domestic and international flights.

Easy to install displays — Surface mount or recessed in the counter for optimal operator visibility.

Quick disconnect — For easy service or replacement.

Bi-directional RS-232 output — For computer interface. Records weights by customer or by flight or get automatic system calculation of additional charges for excess baggage.

Approvals:

UL, NTEP Class III, Canadian Weights and measures

Operating temperature:

Standard: 117VAC $\pm 10\%$, 50/60 Hz, 5 watts maximum
Optional: 230VAC $\pm 10\%$ 50/60 Hz, 5 watts maximum

Warranty: Two year limited warranty applies

Weigh-Tronix Inc

1000 Armstrong Dr
Fairmont, MN 56031-1000, USA
Telephone +1 507-238-4461
Facsimile +1 507-238-4195
e-mail: industrial@weigh-tronix.com
www.weigh-tronix.com

Staveley Weighing & Systems Canada Inc

217 Brunswick Blvd
Pointe Claire, Quebec, Canada H9R 4R7
Telephone +1 514-695-0380
Facsimile +1 514-695-6820



WEIGH-TRONIX

Weighing Products & Systems